



SAFETY DATA SHEET

Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.

According to Regulation (EC) No 1907/2006, Annex II, as amended.

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Electrostatic Thermoset Powder Coating

Product SDS code ELM4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial use.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Element Boya San. ve Tic. A.Ş.
Birlik OSB Mah. 6. Sok. No: 5
34953 Tuzla İstanbul Turkey
Tel: +90 216 593 29 80
Fax: +90 216 593 29 81
E-mail: element@elementboya.com

1.4. Emergency telephone number

Emergency telephone Element Boya: +90 216 593 29 80 (08:00 - 18:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Eye Dam. 1 - H318 Skin Sens. 1 - H317 Muta. 1B - H340 Carc. 1B - H350 Repr. 1A - H360Df STOT RE 2 - H373

Environmental hazards Aquatic Chronic 2 - H411

Additional information Classification (Regulation (EC) No. 1272/2008).

2.2. Label elements

Hazard pictograms



Signal word

Danger

Hazard statements

H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H340 May cause genetic defects.
H350 May cause cancer.
H360Df May damage the unborn child. Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.
According to Regulation (EC) No 1907/2006, Annex II, as amended.
According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Precautionary statements	<p>P260 Do not breathe dust.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	lead sulfochromate yellow, 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

<p>Lead sulfochromate yellow 0,5-20%</p> <p>CAS number: 1344-37-2 EC number: 215-693-7</p> <p>M factor (Acute) = 1 M factor (Chronic) = 1</p> <p>Lists:REACH ANNEX XVII.This substance is in the Candidate List of SVHC for authorisation.</p>
<p>Classification</p> <p>Carc. 1B - H350</p> <p>Repr. 1A - H360Df</p> <p>STOT RE 2 - H373</p> <p>Aquatic Acute 1 - H400</p> <p>Aquatic Chronic 1 - H410</p>
<p>1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione 3-5%</p> <p>CAS number: 2451-62-9 EC number: 219-514-3</p> <p>Lists:REACH ANNEX XVII.This substance is in the Candidate List of SVHC for authorisation.</p>
<p>Classification</p> <p>Acute Tox. 3 - H301</p> <p>Acute Tox. 3 - H331</p> <p>Eye Dam. 1 - H318</p> <p>Skin Sens. 1 - H317</p> <p>Muta. 1B - H340</p> <p>STOT RE 2 - H373</p> <p>Aquatic Chronic 3 - H412</p>

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.

According to Regulation (EC) No 1907/2006, Annex II, as amended.

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin contact	Brush off loose particles from skin. It is important to remove the substance from the skin immediately. In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognised skin cleansing agent. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Dust may irritate the respiratory system. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
Ingestion	May cause sensitisation or allergic reactions in sensitive individuals. May cause discomfort if swallowed. May cause stomach pain or vomiting. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
Skin contact	May cause skin sensitisation or allergic reactions in sensitive individuals. Prolonged contact may cause dryness of the skin. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
Eye contact	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Extinguish with foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	None known.
-------------------------	-------------



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.

According to Regulation (EC) No 1907/2006, Annex II, as amended.

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of dust.

6.2. Environmental precautions

Environmental precautions

Insoluble in water. Aquatic toxicity is unlikely to occur. However, large or frequent spills may have hazardous effects on the environment. Collect spillage. Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Avoid generation and spreading of dust. Small Spillages: Remove spillage with vacuum cleaner or collect with a shovel and broom, or similar. Large Spillages: Collect spillage with a shovel and broom, or similar and reuse, if possible. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Keep container tightly sealed when not in use. Avoid handling which leads to dust formation. May cause cancer. May damage the unborn child. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Suspected of damaging fertility. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.

According to Regulation (EC) No 1907/2006, Annex II, as amended.

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store at temperatures between 5°C and 25°C.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

OEL: 3 mg/m³

1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione

Long-term exposure limit (8-hour TWA): WEL 0.1 mg/m³

Carc

WEL = Workplace Exposure Limit.

Carc = Capable of causing cancer and/or heritable genetic damage.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment that provides appropriate eye and face protection should be worn. The following protection should be worn: Dust-resistant, chemical splash goggles.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.

According to Regulation (EC) No 1907/2006, Annex II, as amended.

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.
Environmental exposure controls	Not regarded as dangerous for the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder.
Colour	Various colours.
Odour	Odourless.
Odour threshold	No information available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	Not applicable.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 20 g/m ³ Upper flammable/explosive limit: 70 g/m ³
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	No information available.
Density or relative density	1,2 -1,9 g/cm ³ @20 °C
Bulk density	No information available.
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Oxidising properties	No information available.
Particle characteristics	No information available.
Softening point	>50 °C



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.
According to Regulation (EC) No 1907/2006, Annex II, as amended.
According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

9.2. Other information

Particle size	30-50 µm
Volatile organic compound	0,0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See the other subsections of this section for further details.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 2,040.82

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 61.22

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Eye Dam. 1 - H318 Causes serious eye damage.



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.

According to Regulation (EC) No 1907/2006, Annex II, as amended.

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation May cause skin sensitisation or allergic reactions in sensitive individuals.

Germ cell mutagenicity

Genotoxicity - in vitro May cause genetic defects.

Carcinogenicity

Carcinogenicity May cause cancer.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Suspected of damaging fertility.

Reproductive toxicity - development

May damage the unborn child.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Aspiration hazard Not relevant. Solid.

General information

Avoid contact during pregnancy/while nursing. May damage fertility. May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. May cause genetic defects. Dust may irritate the eyes and the respiratory system. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Dust may irritate the respiratory system. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

Ingestion

May cause sensitisation or allergic reactions in sensitive individuals. May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact

May cause skin sensitisation or allergic reactions in sensitive individuals. Prolonged contact may cause dryness of the skin.

Eye contact

Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.

Route of exposure

Ingestion Inhalation Skin and/or eye contact

Target organs

No specific target organs known.

Medical considerations

Skin disorders and allergies.

11.2. Information on other hazards

Information on other hazards

This product does not contain any known or suspected endocrine disruptors.

Toxicological information on ingredients.



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.
According to Regulation (EC) No 1907/2006, Annex II, as amended.
According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

	1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione
<i>Acute toxicity - oral</i>	
ATE oral (mg/kg)	100.0
<i>Acute toxicity - inhalation</i>	
ATE inhalation (vapours mg/l)	3.0

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

Lead sulfochromate yellow

<i>Acute aquatic toxicity</i>	
LE(C) ₅₀	0.1 < L(E)C50 ≤ 1
M factor (Acute)	1
<i>Chronic aquatic toxicity</i>	
M factor (Chronic)	1

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility The product is insoluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Endocrine disrupting properties

Endocrine disrupting properties The product does not contain any endocrine disrupting substance.

12.7. Other adverse effects

Other adverse effects None known.



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.

According to Regulation (EC) No 1907/2006, Annex II, as amended.

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

General	For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.
14.1. UN number or ID number	
UN No. (ADR/RID)	3077
UN No. (IMDG)	3077
UN No. (ICAO)	3077
UN No. (ADN)	3077
14.2. UN proper shipping name	
Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS lead sulfochromate yellow)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS lead sulfochromate yellow)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS lead sulfochromate yellow)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS lead sulfochromate yellow)
14.3. Transport hazard class(es)	
ADR/RID class	9
ADR/RID classification code	M7
ADR/RID label	9
IMDG class	9
ICAO class/division	9
ADN class	9



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.

According to Regulation (EC) No 1907/2006, Annex II, as amended.

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-A, S-F
ADR transport category	3
Emergency Action Code	2Z
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(-)

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk according to IMO instruments Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EH40/2005 Workplace exposure limits.
Commission Regulation (EU) 2020/878 of 18 June 2020.
Commission Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Authorisations (SI 2020 No. 1577 Annex XIV) and REACH 1907/2006, Annex XIV No specific authorisations are known for this product.



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.
According to Regulation (EC) No 1907/2006, Annex II, as amended.
According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Restrictions (SI 2020 No. 1577 Annex XVII) and REACH 1907/2006, Annex XVII Restricted to industrial use and to approved professionals - verify where use is allowed.
Entry number: 63

Seveso Directive - Control of major accident hazards E2 Lower-tier 200 tonnes Upper-tier 500 tonnes.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IATA: International Air Transport Association. ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate. LC50: Lethal Concentration to 50 % of a test population. LD50: Lethal Dose to 50% of a test population (Median Lethal Dose). EC ₅₀ : 50% of maximal Effective Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.
Classification abbreviations and acronyms	Carc. = Carcinogenicity Eye Dam. = Serious eye damage Muta. = Germ cell mutagenicity Repr. = Reproductive toxicity Skin Sens. = Skin sensitisation STOT RE = Specific target organ toxicity-repeated exposure Aquatic Chronic = Hazardous to the aquatic environment (chronic)
Key literature references and sources for data	Source: European Chemicals Agency, http://echa.europa.eu/ This SDS is prepared based on the information and documents received from product owner. CRAD or/and SDS author shall not be responsible for incorrect prepared of SDS and pecuniary loss or intangible damages because of deficient or wrong information and documents which comes from product owner.
Classification procedures according to SI 2019 No. 720	Eye Dam. 1 - H318: STOT RE 2 - H373: Skin Sens. 1 - H317: Muta. 1B - H340: Carc. 1B - H350: Repr. 1A - H360Df: : Calculation method. Aquatic Chronic 2 - H411: : Calculation method.
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	SDS has been revised under the current regulations.
Issued by	Büşra Tarakci / CRAD gbf@crad.com.tr Tel.:+90 216 3354600
Revision date	03/01/2024
Revision	2.0



Electrostatic Thermoset Powder Coating

Commission Regulation (EU) 2020/878 of 18 June 2020.

According to Regulation (EC) No 1907/2006, Annex II, as amended.

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Supersedes date	03/10/2019
SDS number	9520
Hazard statements in full	H301 Toxic if swallowed. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H331 Toxic if inhaled. H340 May cause genetic defects. H350 May cause cancer. H360Df May damage the unborn child. Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.